# Video Management Unit (VMU)

Rugged Video & Data Processor



## Overview

The VMU is a generic COTS-based rugged video and data processor, originally developed as an upgrade for ESA's Fluid Science Lab (FSL) on ISS Columbus and designed to manage state-of-the-art scientific cameras and sensors.

The system contains a radiation tolerant space-grade commercial computer unit for system monitoring and management, and for interfacing to the payload host (Columbus / FSL in the case of FSL VMU MkII). These data interfaces are implemented via MIL-STD-1553B, optical TAXI and discrete lines. Gigabit Ethernet can be used instead.

Towards the scientific instruments, a multitude of standard and custom interfaces are provided: GigE, USB 2.0, LVDS, RS422 UART, RS232 UART, and bidirectional LVTTL/RS422 trigger lines.

A powerful Intel Core i7 based ruggedised industrial grade CompactPCI Serial computer is provided for interfacing the scientific instruments and performing data storage, compression, routing, on-line processing and offline processing. The system also provides TCL-based scripting facilities for effective scientific experiment run execution.

2 TB of on-board storage is provided through an array of harddisks. Data downlink to ground is provided through an optical TAXI interface or via Gigabit Ethernet.

The boards of the CompactPCI can easily be replaced by a crew in case of failure.

This mitigates the reliability concerns related to the use of industrial grade COTS boards.

The FSL VMU MkII system developed for FSL was customised at the level of power, data, thermal, and mechanical interfaces. Different configurations are possible. Changing the type of data interfaces is made easy through the use of the industry-standard CompactPCI Serial platform. Customisation of the data handling and processing is made easy through the use of a Linux platform, with packetised software management.

In its initial configuration, power consumption is around 100W, weight around 23kg, and volume around 90,000cm<sup>3</sup>. Options for a mass of 18kg and volume of 45,000cm<sup>3</sup> are available.

High performance Military-grade circular connectors are used throughout (except on the COTS boards), while integrated EMI/power filtering is designed to meet power input voltage, spikes, surges, transients, and EMI/EMC compatibility requirements of typical space deployments.

The VMU allows for video and data management across operating temperature ranges, shock/vibration and radiation conditions representative of a deployment on ISS, and has been fully tested against launch conditions on Cygnus/SpaceX/HTV and operations conditions aboard ISS/Columbus. TRL of the system is 8. Launch of FSL VMU MkII is manifested on SpaceX-15 in June 2018.

#### **APPLICATIONS**

High-performance scientific video and data acquisition with advanced synchronisation and time-tagging functionality, and custom data processing, storage and routing.

### **SERVICES AVAILABLE**

- Custom data acquisition and processing
- Unit support
- Unit customisation

For more information please visit: https://www.spaceapplications.com/

or contact us:
Martin.Ursik@spaceapplications.com

### **OTHER SERVICES**

- Mobility / Rover Operations
- Traverse planning & Execution
- Space Weather Services
- Robotics operations
- Mission / System Simulator

## ABOUT SPACE APPLICATIONS SERVICES

Space Applications Services NV/SA is an independent Belgian company founded in 1987, with a subsidiary in Houston, USA.

Our aim is to research and develop innovative systems, solutions and products and provide services to the aerospace and security markets and related industries. Our activities cover manned and unmanned spacecraft, launch/re-entry vehicles, control centres, robotics and a wide range of information systems.









# Video Management Unit (VMU)

Rugged Video & Data Processor



# **Product Roadmap**

Beyond the current configuration of the VMU, known as FSL VMU MkII, derived designs are expected to be developed for other ISS payloads. While the FSL VMU MkII follows the standard TC/TM paradigm, the use of direct TCP/IP connectivity to the VMU can be easily implemented for a more powerful and flexible operation of the VMU.

# **Applications**

The VMU is specifically designed for the data and video management of scientific payloads needing high data rates and complex processing. Its modular design and use of industry-grade COTS frontends allows for customisation at the level of interfaces and functionality at minimal cost.

## **Features**

- MIL-STD-1553B interface for TC/TM, time distribution, file transfer, and RT/RT transfer.
- Optical 32 Mbps TAXI interface for High Rate Data transfer.
- Tailoring of the capabilities and functions needs by the targeted mission and spacecraft
- Possibility of Gigabit Ethernet interface for TC/TM, time distribution, file transfer, and high rate science data transfer.
- External monitoring and control via 5V bi-level status/command and thermistors.

- 3 Gigabit Ethernet interfaces for scientific instruments, 1 for connection to on-board Laptop.
- Control and acquisition of up to 3 GigE Vision 1.1/2.0 cameras.
- 2 USB 2.0 interfaces.
- 1 Mbps RS422 UART interface for TC/TM and data transfer with experiment.
- Bi-directional RS422 and LVTTL triggering with softwareconfigurable behaviour.
- Proprietary LVDS/RS232 interface for Thermoteknix 640FF thermal camera.
- Legacy LVDS/RS422 interface for Kodak ES1.0 digital cameras.
- Legacy interface for NTSC analogue cameras.
- 2 TB of harddisk-based storage (size and RAID configuration van be customised).
- Data handling: complex operations scenarios involving storage, replay, downlink, Crew visualisation, compression, online processing, offline processing.
- Compression: JPEG, PNG, H.264, frame dropping, region-of-interest, scaling, custom data processing via customer-provided software.
- Designed to meet ISS internal environmental conditions (shock, vibration, radiation, temperature).











# Video Management Unit (VMU)

Rugged Video & Data Processor



- Designed to meet MIL-STD-461F EMI/EMC (conducted & radiated emissions & susceptibility) and to survive to typical power input and transients.
- Multi-threaded software architecture on 64bit Linux operating system with packaged software management.
- High-performance Military grade circular connectors.

## Reliability:

 MTBF of core system (excluding Crew-replaceable industrial grade boards): 243000h (Calculated per MIL-HDBK-217F).

#### **APPLICATIONS**

High-performance scientific video and data acquisition with advanced synchronisation and time-tagging functionality, and custom data processing, storage and routing.

### **SERVICES AVAILABLE**

- Custom data acquisition and processing
- Unit support
- Unit customisation

For more information please visit: <a href="https://www.spaceapplications.com/">https://www.spaceapplications.com/</a>

or contact us:
Martin.Ursik@spaceapplications.com

## **OTHER SERVICES**

- Mobility / Rover Operations
- Traverse planning & Execution
- Space Weather Services
- Robotics operations
- Mission / System Simulator

## ABOUT SPACE APPLICATIONS SERVICES

Space Applications Services NV/SA is an independent Belgian company founded in 1987, with a subsidiary in Houston, USA.

Our aim is to research and develop innovative systems, solutions and products and provide services to the aerospace and security markets and related industries. Our activities cover manned and unmanned spacecraft, launch/re-entry vehicles, control centres, robotics and a wide range of information systems.







